


订货代号 TO ORDER



- | | |
|--|--|
| <p>1 功能
LDR= 直动式过载阀
Direct-Acting Relief Valve</p> <hr/> <p>2 流量 Capacity
D=95L/min</p> <hr/> <p>3 控制方式 Control
L=Standard Screw Adjustment
K=Handknob</p> <hr/> <p>5 油封 Seal Kits
N= 丁晴橡胶 Buna N
V= 氟橡胶 Viton</p> <hr/> <p>6 阀块油口 Body Porting
空白 Blank= 不带阀块 None
6T=SAE6
8T=SAE8
2G=G 1/4
3G=G 3/8</p> | <p>4 弹簧调压范围 Spring Ranges
A=500-3000psi (35-210bar)
Preset:1000psi (70bar)
W=800-4500psi (55-315bar)
Preset:1000psi (70bar)
B=300-1500psi (20-105bar)
Preset:1000psi (70bar)
C=1000-6000psi (70-420bar)
Preset:1000psi (70bar)
D=200-800psi (14-55bar)
Preset:400psi (28bar)
S=50-200psi (3.5-14bar)
Preset:100psi (7bar)</p> <p>Factory pressure setting established at 15L/min;
工厂的设定是指溢流阀开启 [流量为 15L/min] 时的压力 ;</p> |
|--|--|

安装尺寸 INSTALLATION DIMENSIONS

